

CHANGING TO A NEW COMBINATION

Make up a new combination, selecting 3 sets of numbers of your own choosing. DO NOT use numbers between 0 and 20 for your last number (e.g.. 52 - 86 - 13).

For maximum security, DO NOT use numbers ending in 0 or 5 and DO NOT use numbers in a rising or falling sequence (e.g.. 32 - 48 - 74 or 74 - 48 - 32).


1. Dial the existing combination as explained in the previous paragraphs 1,2 and 3 but using the changing index for the alignment of the numbers.
2. Hold the dial with the last number at the changing index, and insert the change key in the key hole in the back of the lock (See Figure 3.) Insert the key until the wing is entirely inside the lock and comes to a positive stop (See Figure 2.)
3. Turn key one quarter turn to the LEFT (See Figure 3.) Tumbler wheels are now in an unlock position for setting a new combination.
4. Dial the new combination as explained in the previous paragraphs 1,2 and 3 using the changing index for the alignment of the numbers.
5. Hold the dial with the last number at the changing index. Turn the change key back to the RIGHT one quarter turn (See Figure 4.) and remove it from the lock. The new combination you have selected is now set in the lock.

CAUTION

BEFORE CLOSING THE DOOR, operate the new combination several times using the opening index to ensure new combination has been set correctly before the door is shut and locked.

If an error has been made setting a new combination we suggest an accredited locksmith be called. This is not covered with your warranty.

Figure 2..



Wing on Key passes thru slot
in lock plate

Figure 3.




Figure 4.

